

# Sample Exam Questions

---

The sample exam questions that follow illustrate the relationship between the course framework and the AP Computer Science A Exam and serve as examples of the types of questions that appear on the exam. After the sample questions is a table that shows to which skill, learning objective(s), and unit each question relates. The table also provides the answers to the multiple-choice questions.

## Section I: Multiple-Choice

1. Consider the following code segment.

```
int a = 5;
int b = 2;
double c = 3.0;
System.out.println(5 + a / b * c - 1);
```

What is printed when the code segment is executed?

- (A) 0.6666666666666667
  - (B) 9.0
  - (C) 10.0
  - (D) 11.5
  - (E) 14.0
2. Consider the `processWords` method. Assume that each of its two parameters is a `String` of length two or more.

```
public void processWords(String word1, String word2)
{
    String str1 = word1.substring(0, 2);
    String str2 = word2.substring(word2.length() - 1);
    String result = str2 + str1;
    System.out.println(result.indexOf(str2));
}
```

Which of the following best describes the value printed when `processWords` is called?

- (A) The value `0` is always printed.
  - (B) The value `1` is always printed.
  - (C) The value `result.length() - 1` is printed.
  - (D) A substring containing the last character of `word2` is printed.
  - (E) A substring containing the last two characters of `word2` is printed.
3. Which of the following statements assigns a random integer between 25 and 60, inclusive, to `rn`?
- (A) `int rn = (int) (Math.random() * 25) + 36;`
  - (B) `int rn = (int) (Math.random() * 25) + 60;`
  - (C) `int rn = (int) (Math.random() * 26) + 60;`
  - (D) `int rn = (int) (Math.random() * 36) + 25;`
  - (E) `int rn = (int) (Math.random() * 60) + 25;`
4. Vehicles are classified based on their total interior volume. The `classify` method is intended to return a vehicle classification `String` value based on total interior volume, in cubic feet, as shown in the table below.

Vehicle size class	Total interior volume
Minicompact	Less than 85 cubic feet
Subcompact	85 to 99 cubic feet
Compact	100 to 109 cubic feet
Mid-Size	110 to 119 cubic feet
Large	120 cubic feet or more

The `classify` method, which does not work as intended, is shown below.

```
public static String classify(int volume)
{
    String carClass = "";
    if (volume >= 120)
    {
        carClass = "Large";
    }
    else if (volume < 120)
    {
        carClass = "Mid-Size";
    }
    else if (volume < 110)
    {
        carClass = "Compact";
    }
    else if (volume < 100)
    {
        carClass = "Subcompact";
    }
}
```

```

    else
    {
        carClass = "Minicompact";
    }
    return carClass;
}

```

The `classify` method works as intended for some but not all values of the parameter `volume`. For which of the following values of `volume` would the correct value be returned when the `classify` method is executed?

- (A) 80
  - (B) 90
  - (C) 105
  - (D) 109
  - (E) 115
5. Which of the following best describes the value of the Boolean expression shown below?
- ```
a && !(b || a)
```
- (A) The value is always `true`.
  - (B) The value is always `false`.
  - (C) The value is `true` when `a` has the value `false`, and is `false` otherwise.
  - (D) The value is `true` when `b` has the value `false`, and is `false` otherwise.
  - (E) The value is `true` when either `a` or `b` has the value `true`, and is `false` otherwise.
6. Consider the following code segment.
- ```

int val = 48;
int div = 6;
while ((val % 2 == 0) && div > 0)
{
    if (val % div == 0)
    {
        System.out.print(val + " ");
    }
    val /= 2;
    div--;
}

```

What is printed when the code segment is executed?

- (A) 48 12 6
- (B) 48 12 6 3
- (C) 48 12 6 3 1
- (D) 48 24 12 6
- (E) 48 24 12 6 3

7. Consider the following class definition.

```
public class Example
{
    private int x;
    // Constructor not shown.
}
```

Which of the following is a correct header for a method of the `Example` class that would return the value of the `private` instance variable `x` so that it can be used in a class other than `Example`?

- (A) `private int getX()`
  - (B) `private void getX()`
  - (C) `public int getX()`
  - (D) `public void getX()`
  - (E) `public void getX(int x)`
8. In the following code segment, assume that the string `str` has been properly declared and initialized. The code segment is intended to print the number of strings in the array `animals` that have `str` as a substring.

```
String[] animals = {"horse", "cow", "goat", "dog",
                   "cat", "mouse"};

int count = 0;
for (int i = 0; i <= animals.length; i++)
{
    if (animals[i].indexOf(str) >= 0)
    {
        count++;
    }
}
System.out.println(count);
```

Which of the following changes should be made so the code segment works as intended?

- (A) The Boolean expression in the for loop header should be changed to `i < animals.length`.
- (B) The Boolean expression in the for loop header should be changed to `i < animals.length - 1`.
- (C) The Boolean expression in the for loop header should be changed to `i < animals[i].length`.
- (D) The condition in the `if` statement should be changed to `animals[i].equals(str)`.
- (E) The condition in the `if` statement should be changed to `animals[i].substring(str)`.

9. Consider an integer array, `nums`, which has been declared and initialized with one or more integer values. Which of the following code segments updates `nums` so that each element contains the square of its original value?

I.

```
int k = 0;
while (k < nums.length)
{
    nums[k] = nums[k] * nums[k];
}
```

II.

```
for (int k = 0; k < nums.length; k++)
{
    nums[k] = nums[k] * nums[k];
}
```

III.

```
for (int n : nums)
{
    n = n * n;
}
```

- (A) II only
- (B) I and II only
- (C) I and III only
- (D) II and III only
- (E) I, II, and III

10. Consider the following code segment.

```
ArrayList<String> numbers = new ArrayList<String>();
numbers.add("one");
numbers.add("two");
numbers.add(0, "three");
numbers.set(2, "four");
numbers.add("five");
numbers.remove(1);
```

Which of the following represents the contents of `numbers` after the code segment has been executed?

- (A) ["one", "four", "five"]
- (B) ["three", "two", "five"]
- (C) ["three", "four", "two"]
- (D) ["three", "four", "five"]
- (E) ["one", "two", "three", "four", "five"]

11. Consider the following method, which is intended to return a list containing the elements of the parameter `myList` with all even elements removed.

```
public static ArrayList<Integer> removeEvens
    (ArrayList<Integer> myList)
{
    for (int i = 0; i < myList.size(); i++)
    {
        if (myList.get(i) % 2 == 0)
        {
            myList.remove(i);
        }
    }
    return myList;
}
```

Which of the following best explains why the code segment does not work as intended?

- (A) The code segment causes an `IndexOutOfBoundsException` for all lists because of an incorrect Boolean expression in the for loop.
- (B) The code segment causes an `IndexOutOfBoundsException` for lists with at least one even element because the indexes of all subsequent elements change by one when a list element is removed.
- (C) The code segment returns a list with fewer elements than intended because it fails to consider the last element of `myList`.
- (D) The code segment removes the wrong elements of `myList` because the condition in the `if` statement to test whether an element is even is incorrect.
- (E) The code segment skips some elements of `myList` because the indexes of all subsequent elements change by one when a list element is removed.

12. Consider the following code segment.

```
int[][] points = {{11, 12, 13, 14, 15},
                 {21, 22, 23, 24, 25},
                 {31, 32, 33, 34, 35},
                 {41, 42, 43, 44, 45}};
for (int row = 0; row < points.length; row++)
{
    for (int col = points[0].length - 1;
         col >= row; col--)
```

```

    {
        System.out.print(points[row][col] + " ");
    }
    System.out.println();
}

```

What is printed when this code segment is executed?

(A) 15 14

```

25 24 23
35 34 33 32
45 44 43 42 41

```

(B) 15 14 13 12

```

25 24 23
35 34
45

```

(C) 11 12 13 14 15

```

21 22 23 24
31 32 33
41 42

```

(D) 15 14 13 12 11

```

25 24 23 22
35 34 33
45 44

```

(E) 15 14 13 12 11

```

25 24 23 22 21
35 34 33 32 31
45 44 43 42 41

```

13. Consider the following code segment.

```

int[][] arr = {{1, 2, 3, 4},
               {5, 6, 7, 8},
               {9, 10, 11, 12}};

int sum = 0;
for (int[] x : arr)
{
    for (int y = 0; y < x.length - 1; y++)
    {
        sum += x[y];
    }
}

```

What is the value of `sum` as a result of executing the code segment?

(A) 36

(B) 54

(C) 63

(D) 68

(E) 78

14. Consider the following class definitions.

```
public class Thing1
{
    public void calc(int n)
    {
        n *= 3;
        System.out.print(n);
    }
}
```

```
public class Thing2 extends Thing1
{
    public void calc(int n)
    {
        n += 2;
        super.calc(n);
        System.out.print(n);
    }
}
```

The following code segment appears in a class other than `Thing1` or `Thing2`.

```
Thing1 t = new Thing2();
t.calc(2);
```

What is printed as a result of executing the code segment?

- (A) 4
  - (B) 6
  - (C) 68
  - (D) 124
  - (E) 1212
15. Consider the following two methods, which are intended to return the same values when they are called with the same positive integer parameter `n`.

```
public static int mystery1(int n)
{
    if (n > 1)
    {
        return 5 + mystery1(n - 1);
    }
    else
    {
        return 1;
    }
}
```



```

public static int mystery2(int n)
{
    int total = 0;
    int x = 1;
    while (x < n)
    {
        total += 5;
        x++;
    }
    return total;
}

```

Which, if any, of the following changes to `mystery2` is required so that the two methods work as intended?

- (A) The variable `total` should be initialized to 1.
- (B) The variable `x` should be initialized to 0.
- (C) The condition in the `while` loop header should be `x < n - 1`.
- (D) The condition in the `while` loop header should be `x <= n`.
- (E) No change is required; the methods, as currently written, return the same values when they are called with the same positive integer parameter `n`.

## Section II: Free-Response

The following are examples of the kinds of free-response questions found on the exam. Note that on the actual AP Exam, there will be four free-response questions.

### Methods and Control Structures (Free-Response Question 1 on the AP Exam)

This question involves the use of *check digits*, which can be used to help detect if an error has occurred when a number is entered or transmitted electronically. An algorithm for computing a check digit, based on the digits of a number, is provided in part (a).

The `CheckDigit` class is shown below. You will write two methods of the `CheckDigit` class.

```

public class CheckDigit
{
    /** Returns the check digit for num, as described in part (a).
     * Precondition: The number of digits in num is between one and
     * six, inclusive.
     * num >= 0
     */
    public static int getCheck(int num)
    {
        /* to be implemented in part (a) */
    }

    /** Returns true if numWithCheckDigit is valid, or false
     * otherwise, as described in part (b).
     * Precondition: The number of digits in numWithCheckDigit
     * is between two and seven, inclusive.
     */
}

```